

Can onboard energy storage devices reduce the catenary energy consumption?

Abstract: For improving the energy efficiency of railway systems, onboard energy storage devices (OESDs) have been applied to assist the traction and recover the regenerative energy. This article aims to address the optimal sizing problem of OESDs to minimize the catenary energy consumption for practical train operations.

Can onboard energy storage systems be integrated in trains?

As a result, a high tendency for integrating onboard energy storage systems in trains is being observed worldwide. This article provides a detailed review of onboard railway systems with energy storage devices. In-service trains as well as relevant prototypes are presented, and their characteristics are analyzed.

What are on-board energy storage devices (hesds)?

As an emerging technology,on-board HESDs are usually composed of different types of energy storage devices,namely,batteries (BATs),supercapacitors (SCs),and flywheels,where the hybridization solutions to BATs and SCs are widely applied in electric vehicles and rail transportation [5,6].

How much energy does a storage device use?

The storage devices featured 600 Whand 180 kW of rated energy and power, with a total weight of 430 kg and consequent specific energy and power of 1.4 Wh/kg and 418 W/kg, respectively.

What are the advantages and disadvantages of on-board and stationary energy storage?

On-board, stationary and on-board+stationary access schemes have their own advantages and disadvantages. on-board+stationary coordinated energy storage can reduce the energy demand of vehicle ESS and the energy transmission loss of stationary ESS, which helps both methods to better utilize their respective characteristics.

How energy storage device is connected to the grid?

The energy storage device is connected to the grid through voltage source inverter and transformer. Compared with back-to-back structure, its hardware complexity is reduced, but the energy output of the energy storage device is almost equally divided by two arms.

It was established that reducing the mass of the energy storage device, which includes lithium cells and supercapacitors, leads to an increase in the cost of one kilowatt-hour of energy storage capacity, which reduces the attractiveness of capital expenditures for the creation of such an energy storage device. Hybridization of the energy ...

These simulations have obtained an estimation of the charge of the energy storage device, which is needed to design the set of ATO speed profiles in scenarios with an on-board energy storage device installed. Table 6.1 shows the value of the on-board energy storage device charge for one interstation with different initial charge



conditions ...

On-board energy storage devices (OESD) and energy-efficient train timetabling (EETT) are considered two effective ways to improve the usage rate of regenerative braking energy (RBE) of subway trains. EETT is less costly but has lower ceilings, whereas OESD, although expensive, maximizes the reuse of RBE. ...

The storage devices featured 600 Wh and 180 kW of rated energy and power, with a total weight of 430 kg and consequent specific energy and power of 1.4 Wh/kg and 418 W/kg, respectively. Experimental tests on the catenary/EDLC hybrid units showed a modest 1.6% reduction in the peak power demand from the overhead wire during accelerations due to ...

Pc(u,Vc) = VcIc(u)ich ($u \ge 0$) VcIc(u)/ich ($u \le 0$) (14) Ic(u) = uIc max (15) Here, im and ig(v) are motor-inverter efficiency in accelerating and braking respectively. The constant M is the total weight of the train including on-board energy storage. The regenerative efficiency ig must be treated as the function of speedyforconsidering electro ...

They are the most common energy storage used devices. These types of energy storage usually use kinetic energy to store energy. ... Theoretically, the basic function of the capacitor is to store energy. Its common usage includes energy storage, voltage spike protection, and signal filtering. It was invented by a German scientist, Ewal. 6 min read.

Intermittent renewable energy is becoming increasingly popular, as storing stationary and mobile energy remains a critical focus of attention. Although electricity cannot be stored on any scale, it can be converted to other kinds of energies that can be stored and then reconverted to electricity on demand. Such energy storage systems can be based on ...

The main advantages of CAES include long energy storage time (more than one year), short response time (less than 10 min), good part-load performance, high efficiency (70-80%), long asset life (about 40 years), low environmental effects, and flexible capacity range. ... They eliminate the cathode storage device and use semi-solid electrodes ...

DOI: 10.1016/j.cie.2018.09.024 Corpus ID: 53779331; Train speed profile optimization with on-board energy storage devices: A dynamic programming based approach @article{Huang2018TrainSP, title={Train speed profile optimization with on-board energy storage devices: A dynamic programming based approach}, author={Yeran Huang and Lixing Yang ...

In the past few decades, electricity production depended on fossil fuels due to their reliability and efficiency [1]. Fossil fuels have many effects on the environment and directly affect the economy as their prices increase continuously due to their consumption which is assumed to double in 2050 and three times by 2100 [6] g. 1 shows the current global ...



The traction power supply system includes the following main parts: train (Veh), traction substation (TSS), WESS, and OESS. The Kirchhoff voltage law (KVL) of the system is shown in (1). ... Wu C et al (2021) A two-step method for energy-efficient train operation, timetabling and on-board energy storage device management. IEEE Trans Transp ...

Electrochemical energy storage (EcES), which includes all types of energy storage in batteries, is the most widespread energy storage system due to its ability to adapt to different capacities and sizes [].An EcES system operates primarily on three major processes: first, an ionization process is carried out, so that the species involved in the process are ...

Storage technologies devices are very interesting solutions for improving energy saving and guaranteeing contemporaneously to enhance the electrical characteristics of Light Rail Transit (LRT) systems. Onboard Energy Storage System based on Lithium Ion Capacitor (LiC) devices represent a viable engineering solution for energy saving optimization. The authors suggest a ...

The control strategies of energy storage device include constant current control, constant power control [22] and voltage/current double closed loop control [7]. In addition to the control method, the working state of the energy storage device should be selected according to the traction network demand and the remaining capacity of the energy ...

The on-board supercapacitor energy storage system for subway vehicles is used to absorb vehicles braking energy. Because operating voltage, maximum braking current and discharge depth of supercapacitor have a great influence on its rational configuration, there are theoretical optimum values based on the analysis of vehicle regenerative braking theory, whose ...

Other critical factors when selecting an on-board energy storage device include the sizing of the storage device (especially when it comes to EMUs) and safety issues (especially on passenger trains). storage devices can be used on-board railway cars for three main purposes: energy consumption Nima Ghaviha et al. / Energy Procedia 105 (2017 ...

The selection of an energy storage device for various energy storage applications depends upon several key factors such as cost, environmental conditions and mainly on the power along with energy density present in the device. ... The third synthetic method includes polymerization of the monomer of the requisite polymer around the nanoparticles ...

of the energy storage in electrified railway systems is still a new research direction for both stationary energy storage and OESD [3]. Optimal sizing problem for stationary and substation-based energy storage has been studied with no constraints on weight and volume of the energy storage devices. In [27], energy



Web: https://wodazyciarodzinnad.waw.pl